

MADE IN
TAIWAN



Machines may be illustrated with optional accessories

Model:		TY-1640VS	TY-2500	TY-2000	TY-2260VS	TY-2660VS	
Swing over Bed		410 mm (16.14")	460mm (18")		560mm (22")	660mm (26")	
Distance between Centres		1016 mm (40")	1145mm (45")	1600mm (63")	1530mm (60")		
Spindle	Bore	52 mm (2.04")	60mm (2 5/16")		104mm (4 1/16")		
	Nose	D1-6	D1-6		D1-8		
	Speed	2 steps, variable	3 steps, variable		2 steps, variable		
	Motor	7 1/2HP	10HP		15HP		
Coolant System		1/8HP	1/8HP		1/8HP		
Rear Splash Guard		standard	standard		standard		
Chuck Guard		standard	standard		standard		
Micro Stop		standard	standard		standard		
Steady Rest with roller bearings		standard, 1 - 6"	standard, 1 - 6"		standard, 4 - 12"		
Follow Rest		option	option		option		
Equipped with:		8" 3-Jaw D1-6 S/C Prec Steel Chuck, direct mount	10" 3 Jaw S/C Precision Steel Chuck, direct mount		12" 3 Jaw S/C Precision Steel Chuck, direct mount		
		GS2-B Klopfer Quick Change Precision Tool Post Set			GS3-C Klopfer Quick Change Precision Tool Post Set		
		ACU-RITE 2-Axis Digital Readout Installed					

20250507

Visit our showroom with equipment on display and under power



Heinman Machinery Ltd.

6105 Kestrel Rd, Mississauga ON
T 905-564-9479

sales@heinmanmachinery.com
www.heinmanmachinery.com